



# Toppingsmachine

|                            |   |
|----------------------------|---|
| Application:               | Toppings (dry, IQF or moist) such as small amounts of ham cubes, chicken, chickpeas, corn, paprika and other small vegetables, nuts, diced onions, seeds. |
| Drive:                     | Pneumatic   |
| Construction:              | Stainless steel   |
| Dosing range:              | selected volumetric cups, to be defined   |
| Synchronization:           | With tray conveyors, traysealer lines   |
| Versions:                  | Single or dual dosing positions   |
| Capacity:                  | 40-45 strokes per minute<br>Capacity and functionality are related to the products and the packaging line configuration                                   |
| Changeover time:           | Within a few minutes  |
| Frame:                     | Mobile, adjustable in height  |
| Control system:            | Siemens logo  |
| Power:                     | 240V - 50 Hz  |
| Hopper:                    | 30L (option extended hopper)  |
| Compressed air connection: | min. 6 bar.   |
| IP class:                  | IP65  |



SIXPAK B.V.  
Mauritsstraat 8  
The Netherlands  
Phone +31 (0)40-2366825  
info@sixpak-food.eu  
www.sixpak-food.eu

Rabobank  
IBAN: NL70RABO0184887682  
K.v.K: 60954116  
BTW: NL8541.33.434.B01



Chicken shreds on chicken spread



Chickpeas on hummus



Bacon bits on stews